

COMMERCIALISING the "SEARL EFFECT" for ENERGY and PROPULSION SYSTEMS

Review from web site <http://www.sisrc.com/>
Email address: admin@sisrc.com

The "Searl Effect", discovered by J.J.R. Searl, is a method of extracting energy. Some current expressions for the source of this energy being The Space Fabric, Quantum Space Field, and Zero Point Energy.

SISRC Ltd has been formed to develop and license Searl Effect Technology (SET) on a global basis.

THE COMPANY

SISRC Ltd is the company formed to administer the implementation of the Searl Effect Technology, (SET) invented by J. R. R. Searl. SISRC Ltd designs, develops and implements Searl Effect Technology as it is initiated in various applications and territories. SISRC Ltd is the administrative hub of the group and will continue to be based in the UK. SISRC Ltd will grant production and marketing licenses for Searl Effect Technology applications to different companies in specific territories. Currently proposed related companies include:

* SISRC -Germany, SISRC -Iberia, SISRC - Sweden, SISRC - Australia, SISRC New Zealand.

* SISRC -AV (Audio Visual) provides computer graphics presentations of the SET.

BACKGROUND

The Searl Effect Generator (SEG) technology, as applied to the commercial market, had been previously developed to the point where a few prototype SEG generators were made, and used for electricity generation and motion. Commercial interest at that time focused on the SEG's transport potential and, under commercial pressure to deliver a fully functioning system, the original generators were used and lost in a series of vehicular propulsion experiments and demonstrations. Funding was insufficient to continue with the manufacture of the required larger-scale pressurized cabin machines - resulting in the termination of the project at that time.

Although all the operating principles, precise proportions and weights of the required materials are known for three of the four required operating materials, the precise data of the original magnetic layer is uncertain. The objective of the current R&D programme is to re-establish the original magnetic layer using modern and more efficient materials.

Originally, the layered materials were constructed and magnetized by the now-defunct Midlands Electricity Board under the direction of John Searl (see colored photo of the experimental craft construction on the cover page).

Modern magnetic materials have advanced considerably, and old ones discontinued, so a series of tests need to be conducted to establish the optimum materials and processes. These tests need to comply with the working criteria required and must lead to a cost-effective manufacturing process.



Fig.1

Experimental ring and rollers

In recent times SISRC has been re-establishing the original research. Due to the very limited funding that has been available, only a partially functioning demonstration prototype of the SEG principles has been possible. This prototype consists of the innermost of the three composite rings required and several rollers.

We would like to hear from anyone who worked on or was involved with Searl Technology prior to 1983. Also anyone who has any old technical data, photographs or films relating to the technology. Such information could greatly assist this technology to reach the marketplace for the benefit of all and would be dealt with in the strictest of confidence.

TECHNICAL DESCRIPTION

Physically the Searl Effect Generator (SEG) consists of three concentric rings each made of a composite of four different materials which are also concentrically attached to each other. The three rings are fixed to a base. Surrounding each of the rings, and free to rotate around them, are rollers - typically 10 on the first ring, 25 on the next and 35 on the outer ring. Surrounding the rollers on the outer ring are coils which are connected in various configurations to supply either AC or DC current at a variety of voltages.

Multiple magnetic poles are imprinted on the rings and rollers to form frictionless magnetic bearings. These also arrange the static charge into opposing charge clusters which cause the rollers to rotate around the circumference of the ring (as shown in Fig. 2).

Some expressions currently in use to describe the source of the energy for the SEG are The Space Fabric, Quantum Energy field of Space or Zero Point Energy. This is an unlimited and constant source of energy which can be made to flow when the correctly proportioned masses concerned are stimulated by the correct frequencies creating an 'open system'.

The idea of utilising this source of energy is currently the subject of various devices and experiments such as the 'Lamb shift', 'Casimir Effect' and the work of the Russian Nobel Prize winner Ilya Prigogine. However these devices and experiments tend to only prove the existence of the energy and not a method to create a coherent, ordered flow to produce useful power.



Fig. 2

15 KWt Searl Effect Generator (SEG)

In contrast, John Searl has discovered that, in order to create a steady and stable flow, all the masses of the device (and the stimulating frequencies) must conform to precise values determined mathematically by the 'Law of the Squares'. A machine constructed to these principles produces a stable and useful power output.

**DEFINITION OF A SURFACE OPERATING
S.E.G. (J. Searl) 15.09.00**

A Linear motor operating on a magnetic bearing with the characteristics of an auto-transformer. The S.E.G. is defined as a device, which is constructed from 2,124 component parts, which make up 3 plates and 66 roller sets (see figures on the cover page). 12 of the 2,124 components create the 3 plates, which act

as reaction components. 2,112 components are employed to create 66 roller sets, which act as active components. Each roller set consists of 8 segments constructed from 32 components. Each segment cannot be less than 34 grams in weight, as the law of the squares defines that value as the lowest value suitable for the reasonable generation of electricity. Therefore the smallest roller set must weigh 272 grams, making a grand total of 2,244 grams per roller set for the smallest surface bound SEG.

Tolerance should be about 0.05 gram per roller set. The larger the error the greater is the loss of power within the unit. Therefore the total tolerance for the smallest SEG roller set must not be greater than 3.30 grams - above this factor the SEG will not function. **For the best results, the tolerance across the total 66 roller sets should not exceed 0.05 grams!**




Fig.3

The S.E.G. is a step up rotary transformer. In fact it's a 'three rotary transformers' operational system, within a unit. The inner transformer output is fed in to the input of the second plate which increases the output of the second unit, which output feeds as an input to the final unit, thereby increasing its final output to a very high voltage. Therefore the S.E.G. is just a prime mover for the production of clean electrical energy. The output windings must be designed to step down this output to 240 volts at 15KWt's.

During 1968 it being upon this issue, as development progress both here and in the USA, new findings are being created, and updates will be added to this page, as they are certified. When the SEG rollers are brought into close proximity to the SEG Ring, the Searl Effect resonant magnetic field causes negative ions and electrons to be drawn into and accelerated through the machine. This process is assisted by the highly electron-attracting rare earth metal Neodymium.

The unique mechanical and material arrangement of the SEG pulses the neodymium to continually release and replace the surplus electrons to provide electrical or mechanical power, or both.




Fig.4

DEVELOPMENT

Prior to the production of complete 15KWt Searl Effect Generators (SEGs), a minimum of two demonstration Ring & Roller prototypes are to be produced.

The "Ring" is typical of the innermost of the three rings required to make a complete SEG. The 69-roller sets in a complete three ring SEG are identical. Six roller sets will be made for the prototype inner rings so that the Searl Effect can be demonstrated.

The production of a self-running Ring & Roller prototype will establish the precise sequence and parameters of electrical, magnetising and material processes required

for the SEG and will demonstrate electrical power generation. An operating single inner ring with 1-8 rollers will also determine if a particular material will function correctly and at what level of power output.




Fig. 5

Demonstration ring and rollers

The five phases of the development programme that commenced in October 1999 have been completed and the rollers successfully magnetised with 'Searl Effect' magnetic fields. A sixth phase is now required to apply the technology developed in Phase five to the "Ring". This sixth Phase resulting in a demonstration Ring & Roller prototype has duration of 6 months.



**Scientific Breakthrough
Liberates Energy Users from
Fossil Fuel Dependence**

this planet, now it will also transform the way we create energy" said Charles Shaw, corporate counsel and spokesperson for Genesis World Energy. "The implications for worldwide energy generation and consumption are nothing less than staggering."

Information from
http://www.genesisworldenergy.org/genesis_world_energy.htm

Story originally published by **Diana Echeverria, USA**

The Edison Device

Director of Public Relations
Guy Rome & Associates, Inc.
208-345-4143 208-602-0325 (cell)

The first application of this technology is represented in the "Edison Device", a self-contained, self-sustaining energy generation unit. Roughly the size of an outdoor air conditioning system, the power source can be quickly and easily installed in any home or business to provide virtually unlimited energy from any available water source. The Edison Device utilizes the existing electrical wiring and natural gas plumbing in a home or business to replace the energy provided by utility companies. The home version of the Edison Device produces approximately 30 kWt of combined gas and electrical energy per day. By comparison, the typical home uses between five to six kilowatts per day. The commercial model is capable of producing 100 kilowatts of energy per day. The energy generation portion of the devices has no moving parts. In fact, the only "mechanical" aspects of the equipment are small circulation pumps and micro-valves, making the Edison Device both silent and virtually maintenance-free. A minimum amount of water is used over an estimated 20+ years of service life.

**Technology breakthrough harnesses energy from
the molecular structure of water**

BOISE, ID - Dec. 5, 2002 - Genesis World Energy, a privately funded consortium created by a group of military and space program research and development specialists, today unveiled a scientific breakthrough that allows consumers to easily access the energy contained within the hydrogen and oxygen molecular structure of ordinary water. This scientific breakthrough provides a limitless, low cost and environmentally clean source of energy that can be implemented with minimal cost and effort. The viability of using water as an energy source, previously a theoretical concept, is now a reality. "Water has always been the source of life on